

MULTI BAND

SPECIAL HIGH-ADHESION TAPE, CAN BE PLASTERED

EXCELLENT ADHESION

Its excellent adhesion makes it ideal for application on most surfaces, even at low temperatures.

CAN BE PLASTERED

Technical fabric perfect for subsequent plastering, ensuring excellent visual appeal by allowing the tape to be concealed behind claddings and plaster.

0

DIN 4108-7



CAN BE
PLASTERED



HIGH
STABILITY

COMPOSITION

- 1 support: breathable 2-layer PP membrane
- 2 adhesive: acrylic dispersion without solvents
- 3 release liner: silicone coated paper



TECHNICAL DATA

Properties	standard	value	USC units
Thickness	-	0,6 mm	24 mil
Tensile strength	EN ISO 29864	44,0 N/10 mm	25.1 lbf/in
Adhesion strength on OSB at 90° after 10 minutes	EN 29862	5,0 N/10 mm	2.9 lbf/in
Adhesion strength on OSB at 180° after 10 minutes	EN 29862	9,0 N/10 mm	5.1 lbf/in
Adhesion strength (average) on membrane in PP after 24 hours ⁽¹⁾	EN 12316-2	15,0 N/50 mm	1.7 lbf/in
Shear adhesion strength of the joint on membrane in PP after 24 hours ⁽¹⁾	EN 12317-2	150,0 N/50 mm	17.1 lbf/in
Water vapour transmission (Sd)	EN 1931	< 1 m	> 3.5 US Perm
Application temperature ⁽³⁾	-	> -10 °C	> +14 °F
Resistance to temperature	-	-40/+100 °C	-40/+212 °F
Storage temperature ⁽³⁾	-	+5/+25 °C	+41/+77 °F
Solvents	-	no	-

⁽¹⁾Minimum required value according to DTU 31.2 P1-2 (France): 15 N/50 mm.

⁽²⁾Minimum required value according to DTU 31.2 P1-2 (France): 40 N/50 mm.

⁽³⁾ On dry support and at a temperature > 0 °C. The absence of condensation or frost on the surface must be guaranteed.

⁽⁴⁾Store the product in a cool, dry place for no more than 12 months.

Waste classification (2014/955/EU): 08 04 10.

CODES AND DIMENSIONS

CODE	liner [mm]	B [mm]	L [m]	liner [in]	B [in]	L [ft]	
MULTI60	60	60	25	2.4	2.4	82	10

■ FIELDS OF APPLICATION



■ RELATED PRODUCTS



PRIMER SPRAY
page 112



PLASTER BAND IN
page 90



PLASTER BAND OUT
page 90



PLASTER BAND LITE
page 98



UNIVERSAL

Excellent for sealing the membranes overlapping both inside and outside. Due to the black non-woven fabric support, it is not visible behind discontinuous cladding.

SAFE

Thanks to its special composition, it prevents the uncontrolled passage of air, ensuring constantly perfect air and wind tightness.