

CATCH

SCREWING DEVICE

REDUCED STRESS

CATCH allows even the longest screws to be driven quickly and securely, reducing the risk of bit slippage.

DIFFICULT CORNERS

Particularly useful for screw-driving in corners where the applied force is restricted.



CODES AND DIMENSIONS

CODE	L		Ø		weight		pcs
	[mm]	[in]	[mm]	[in]	[g]	[lbs]	
CATCH	210	8 1/4	41,5	1 5/8	630	1.4	1
CATCHL	207	8 1/8	46	1 13/16	680	1.5	1

VIDEO

Scan the QR Code and watch the video on our YouTube channel



TECHNICAL DATA

	CATCH	CATCHL
Machine support	SW 11,5 hexagonal head	SW 11,5 hexagonal head
Bit connection	1/4"	5/16"
Bit included	TX4050	TX4050L (HBS Ø10) TX5050
Compatible screws	HBS (countersunk head) Ø8 mm 0.32 in	HBS (countersunk head) Ø10 - Ø12 mm 0.40 - 0.48 in
	VGS (countersunk head) Ø9 mm 0.36 in	VGS (countersunk head) Ø11 mm 0.44 in
	VGZ (cylindrical head) Ø9 mm 0.36 in	VGS (countersunk head) Ø13 mm 0.52 in

Further information on the use of the product can be found at www.rothoblaas.com.

